

melex®



melex® N.20

HEARSE

CARGO



TOP SPEED
33 KM/H



UP TO
115 KM
RANGE

www.melex-ev.com

N.20 HEARSE



Aluminium Wheels



Electrically controlled platform



Weather cover



Electrically operated platform



Steering - LHD or RHD



Handles for wreaths



Reverse camera



Front bumper



12v outlet



DAB/FM radio

melex® N.20

Specifications

Model	N.20 HEARSE
Length (mm)	4020
Height (mm)	1810
Without mirrors (mm)	1250
Wheelbase (mm)	2500
Outer turning radius (mm)	4600
Top Speed (kph)	33

Driveline & Battery Options

Drive Motor (kW AC)	5.0
Gear Ratio	20:1 / 16:1
48V FLA Battery Options (Ah)	240, 260
48V Li-ion Battery Options (Kwh)	6,2/9,3/12,4 kWh

Standard Features

Electrically operated stainless steel platform, windshield with wipers, 5,0 kW AC motor, 48V on-board battery charger, LED front & rear lights, 12V output, 10" wheels, windshield with wipers, hydraulic drum brakes, 3-point seat belts

Optional Features

Cross holder, box for ropes, guardrails and non-slip mat, water filling system for Flood Lead Acid (FLA) batteries, heated front windshield, FM or DAB radio with Bluetooth, profiled seats, closed glove compartment, forward drive warning sound, beacons, bumper

All features, functionality and other product specifications are subject to change without notice.

